

POWTEQ PRODUCTS

Please keep contact with POWTEQ if you have any further questions.



Cryo Grinder LM200



Micro Ball Mill GT300



Planetary Ball Mill BM40



Planetary Ball Mill BM6Pro



Mortar Grinder MG200



Twister TW100



Multi-functional Mill CM100M



Portable Cutting Mill CM50



Cutting Mill CM200



Ultra Centrifugal Mill FM200



Knife Mill HM100



Knife Mill HM300



Jaw Crusher JC5



Jaw Crusher JC6



Disc Mill DP100



Vibratory Disc Mill VM3



Sample Divider SD200



Vibratory Sieve Shaker SS2000



3D Mixer M10



Smart Graphite Digester

* Technical improvements will be made without prior notice
* The warranty period of the hosts is two years

Company Headquarter

Address: Rm 513, Bldg 2#, Taihua longqi Plaza, No.19
Huangping Road, Huilongguan, Changping District, Beijing
Tel: +86 (0) 10-82363427
E-mail: oversea.sale@powteq.cn
Website: www.powteq.com

POWTEQ KOREA

Tel : +82-42-825-2689
Fax : +82-42-367-3993
E-mail : sales@powteq-korea.com

**Orbiting Scientific & Technology Sdn Bhd
(Malaysia)**

Tel: +603-9058 6581
Fax: +603-9058 1373
E-mail: enquiry@orbitingscientific.com

Vilitek LLC (Russia)

Tel: +7 495 545-07-08(105)
Fax: +7 495 221-05-76
E-mail: office@vilitek.ru

电子邮箱: marketing@powteq.cn

POWTEQ®



Ultra Centrifugal Mill **FM200**

◇ Ultra Centrifugal Mill FM200

Ultra Centrifugal Mill FM200 applies to a wide range of samples. Based on its high efficiency grinding technology and rich accessories, with two-steps grinding of rotating knife - ring screen system, it can process dry and wet grinding in a very short time for the soft, hard, brittle, fibrous samples.



○ **Sample type:**

Soft, elastic, fibrous, water-bearing, oily, fatty, dry sample

○ **Application fields:**

Agriculture, environment, soil, electronics, RoHS testing, coal, chemistry, plastics, medicine, feed, grain, dry plants, etc.

Application Examples

Before grinding	After grinding	Parameter	
		Sample	plastics
		Rotor	12 teeth rotor ,stainless steel
		Sample characteristic	tough
		Remarks	the sample need to be freezed before grinding
		Time	the sample can be collected immediately after feeding
		Sample	corn
		Rotor	12 teeth rotor ,stainless steel
		Sample characteristic	hard
		Remarks	feed size must be less than 8mm
		Time	the sample can be collected immediately after feeding
		Sample	dog food
		Rotor	12 teeth rotor ,stainless steel
		Sample characteristic	oily
		Remarks	feed size must be less than 8mm
		Time	the sample can be collected immediately after feeding

○ **Diversified application, efficient sample preparation**

- Ecological environment protection: plants (root, stem and leaf, etc.) sample preparation, C.H.N determination
- Coal, coatings sample preparation; ash content, thermal measurement
- Identify the nitrogen composition and protein composition of feed and food
- Secondary fuel, rubbish, plastic, electronic elements, the determination of harmful substances


○ **The grinding art for special samples**

- Plastic and rubber samples will become brittle and easy to grind in liquid nitrogen condition.
- The distance ring sieve and automatic vibratory feeder can be used for grinding heat-sensitive samples such as paint, resin.
- The rotor and ring sieve with wear-resisting coatings can be used for grinding rigid and corrosive materials such as fertilizers, chemicals.



○ **Working principle**

The Ultra Centrifugal Mill can realize two-stage crushing for samples with the rotor and ring sieves. Samples are fed from the hopper with anti-splashing design. Under the effect of high speed centrifugal force, the falling samples and the high speed rotor generate a giant impact force to perform pretreatment for samples; then the samples are sheared, extruded and rubbed again between the rotor and ring sieves. The sample will enter into the collecting pan when the size is less than the aperture of ring sieves. The two-stage crushing guarantees moderate and efficient grinding results. Due to the high crushing efficiency, the period of samples staying in the grinding chamber is quite short so as to avoid changes of sample natures.



◇ Automatic feed device and large sample receiver

- Ultra Centrifugal Mill FM200 can be equipped with an automatic feed device, which can guarantee highly homogeneous grinding results and avoid the risk of sample feed overload.
- The ground samples are collected in a collecting pan, which is convenient for collection without sample loss and prevents cross contamination of samples.
- When using a cyclone or a filter bag, the ground samples can be cooled via airflow and leave the grinding chamber quickly via the collecting pan with an exit. If a vacuum cleaner is connected, the process can be faster and more efficient. The cyclone can be used in conjunction with 250ml or 500ml sample bottles; for large volume samples, the cyclone with the capacity of 3L or 5L can be selected. All parts contacting samples can be removed manually without any tools, and it is quite convenient to clean and install such parts.

○ Features and advantages

- The final fineness less than 40 μm.
- Touch control panel, convenient and quick
- Low noise, reliable operation, easy cleaning.
- Rich accessories for choice ensure the application of diversification.
- The fineness depends on the ring sieve.
- Speed adjustable from 6000-18000rpm.
- Two stage rotor—ring sieve system to realize quickly grinding.
- Rotor diameter 95mm and peripheral speed up to 94.2 m/s ensure efficient grinding.



○ Technical highlights

- The specially designed air passage can guarantee that the grinding chamber has constant airflow to cool rotors and samples.
- There is a double layer wear proof seal ring between the grinding chamber and the driving motor to prevent dust from entering the motor.
- The electronic lock and the mechanical lock form double protection for operators.
- The anti-splashing hopper can effectively prevent feedstock blocking and reduce noises.
- Special adapters can be equipped for large-capacity collections.
- The motor has the function of overload protection, and it continues to run after restarting due to overload.

○ Diversified accessories

Rotor

There are 3 kinds of rotors for choice, 24 teeth, 12 teeth and 6 teeth. The 24 teeth is for the crushing of fine sample, while the 12 teeth for general sample and the 6 teeth for coarse massive sample.


Ring sieves

Final fineness depends on the different aperture ring sieve. We also provide the reinforcing screen to enhance the stability of the ring sieve.

○ The material of all the rotors and the ring sieves not only has stainless steel but also the heavy-metal-free for choice to meet different laboratory requirements.

○ The rotor and the ring sieve are chosen according to the properties of the samples, the required final fineness and subsequent analysis.

○ We offer a special ring sieve with shear function, for most materials, about 80% of the samples can reach the fineness of less than the half aperture size of the sieve used.



collecting pan

○ Technical data

FM200			
Feed size	< 10mm	Rated power	750W
Final fineness	< 40 μm	Power supply	220V, 50/60Hz
Speed	6000-18000rpm	Instrument size	400*506*495mm
Peripheral speed	31.4-94.2m/s	Package size	590*590*630mm
Rotor diameter	98mm	Net weight	38kg
Ring sieve	0.08, 0.12, 0.20, 0.25, 0.50, 0.75, 1.00, 2.00mm		
Collecting pan volume	900ml(volume of the sample collected no more than 300ml)		